

Series 8, built-in oven, 60 x 60 cm, Stainless steel HBG6764S6M











Included accessories

2 x combination grid 1 x universal pan

The built-in oven with top-/bottom heat: achieve perfect results on one level thanks to optimal distribution of heat.

- 4D Hotair: even heat distribution for perfect results on any level.
- TFT Touch Display: clearly shows text and images, for easy and intuitive oven control.
- Pyrolytic self-cleaning: automatically cleans the oven, just wipe out the ash.
- Flap door with SoftOpen and SoftClose: the oven door opens and closes especially gently and quietly.
- 1-stage telescopic rails, fully extendable: for safe, easy insertion and removal of baking trays.

Technical Data

Gross weight: 41.4 kg

Color / Material Front : Stainless steel Built-in / Free-standing : Built-in

Integrated Cleaning system : Pyrolytic+Hydrolytic

Min. required niche size for installation (HxWxD) : 585-595 x

560-568 x 550 mm

Dimensions: 595 x 594 x 548 mm

Dimensions of the packed product (HxWxD): 670 x 680 x 670

mm

Control Panel Material: Stainless steel

Door Material : Glass Net weight : 39.0 kg

Usable volume of cavity: 71 l

Cooking method:, 4D hot air, Bottom heat, Defrost setting, Full width grill, Half width grill, Hot Air-Eco, hot air grilling, low temperature cooking, Pizza setting, pre-heating, Top/bottom

heat, warming

Number of interior lights: 1

Length electrical supply cord: 120 cm

Interior Lights - cavity 1 : 1
Pull-out system : 1-level
Clock function : Alarm, Off, On

Included accessories: 2 x combination grid, 1 x universal pan

Broil Element Wattages cavity 1 : 2800 W Convection Element Wattages cavity 1 : 2200 W

Energy efficiency rating : A+

Energy consumption per cycle conventional (2010/30/EC): 0.87

kWh/cycle

Energy consumption per cycle forced air convection (2010/30/ $\,$

EC): 0.69 kWh/cycle

Energy efficiency index (2010/30/EC) : 81.2 %

Connection Rating: 3600 W Fuse protection: 16 A Voltage: 220-240 V Frequency: 50; 60 Hz Plug type: no plug

Color / Material Front : Stainless steel

Energy input : Electric

Required cutout/niche size for installation (in) : x xDimensions of the packed product : $26.37 \times 26.37 \times 26.77$

Net weight: 86.000 lbs Gross weight: 91.000 lbs

Length electrical supply cord: 120 cm

Net weight: 39.0 kg

Included accessories: 2 x combination grid, 1 x universal pan





Series 8, built-in oven, 60 x 60 cm, Stainless steel HBG6764S6M

The built-in oven with top-/bottom heat: achieve perfect results on one level thanks to optimal distribution of heat.

Type of oven / heating system:

- Oven with 13 heating methods: 4D hot air, Hot Air-Eco, Top/ bottom heat, Conventional heat ECO, hot air grilling, Full width grill, Half width grill, Pizza setting, Bottom heat, low temperature cooking, Defrost setting, Plate warming setting, Hold warm
- Temperature range 30 °C 300 °C
- Cavity volume: 71 l

Design:

- Rotary swivel

Cleaning:

- Pyrolitic self-cleaning
- Full glass inner door

Comfort:

- IC6_CBO_62
- Electronic clock
- soft opening
- baking sensor multipoint temperature probe
- Rapid heating-up
- Halogen interior lighting, Switch for oven illumination
- Integral cooling fan
- Bar handle
- WLAN

Accessory:

- 2 x combination grid, 1 x universal pan

Environment and Safety:

- very low door temperature
- door lock electronical
 Child lock Safety switch Residual heat indicator start button door contact switch

Technical Info:

- Length of mains cable: 120 cm
- Nominal voltage: 220 240 V
- Total connected load electric: 3.6 KW
- Energy efficiency rating (acc. EU Nr. 65/2014): A+
 Energy consumption per cycle in conventional mode:0.87 kWh
 Energy consumption per cycle in fan-forced convection mode:0.69 kWh


Number of cavities: 1 Heat source: electrical Cavity volume:71

Dimensions:

- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- "Please reference the built-in dimensions provided in the installation drawing"



Series 8, built-in oven, 60 x 60 cm, Stainless steel HBG6764S6M



measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm

