

**Series 2, canopy cooker hood, 53 cm,
Stainless steel
DLN53AA50B**



The canopy cooker hood: offers you flexibility in your kitchen planning - mount it either on the wall or above a kitchen island.

- **Silent:** maximal extractor performance with little noise
- **LED-Illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- With exhaust, the air is cleaned by a grease filter and then ducted to the outside which ensures optimal kitchen air quality.
- 3-Speed Power Level Options To Suit Your Cooking Style And Recipes
- Slide Switch Control

Technical Data

Typology : Built-in/Built-under
 Length electrical supply cord : 150 cm
 Min. required niche size for installation (HxWxD) : 208mm x 493.0mm x 257mm mm
 Net weight : 4.5 kg
 Type of control : mechanical
 Number of speed settings : 3
 Maximum output air extraction : 300 m³/h
 Maximum output recirculating air : 300 m³/h
 Number of lights : 2
 Noise level : 61 dB(A) re 1 pW
 Diameter of air outlet : 120 mm
 Grease filter material : Washable aluminium
 Odour filter : No
 Operating Mode : Convertible
 Optional accessories : DWZ0IN0A0, DWZ0IN0T0
 Total power of the lamps : 6 W
 Grease filter type : Kasette
 Connection Rating : 121 W
 Fuse protection : 5 A
 Voltage : 220-240 V
 Frequency : 50 Hz
 Plug type : GB plug
 Installation typology : Built-in
 Material body : Stainless steel
 Plug type : GB plug
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product : 10.74 x 31.53 x 12.67
 Net weight : 10.000 lbs
 Gross weight : 17.000 lbs
 Motor location : Integrated motor in hood body
 No-return airflow flap : Yes
 Length electrical supply cord : 150 cm
 Dimensions of the product, with chimney (if exists) : x 534.0 x 300.0 mm
 Dimensions of the packed product (HxWxD) : 273 x 801 x 322 mm
 Net weight : 4.5 kg
 Gross weight : 7.6 kg



4 242005 124909

**Series 2, canopy cooker hood, 53 cm,
Stainless steel
DLN53AA50B**

**The canopy cooker hood: offers you
flexibility in your kitchen planning - mount it
either on the wall or above a kitchen island.**

Variant:

Design:

- Canopy hood

Comfort:

- Suitable for ducted or re-circulated extraction
- For installation in a modified cupboard, above a hob
- Sliding switch control for extractor speeds and light
- 3 speeds
- Paper grease filter with saturation indicator

Environment and safety:

- Energy Efficiency Class: D*
- Average Energy Consumption: 66.7 kWh/year*
- Blower Efficiency Class: E*
- Lighting Efficiency Class: D*
- Grease Filtering Efficiency Class: D*

Technical information:

- Power rating: 121 W
- Noise min./max. Normal Level: 46/61 dB*
- Light Intensity: 78 lux
- Colour Temperature: 2700 K

Measures:

- 120 mm diameter pipe

Optional accessories

- Charcoal odour filter DHZ7304
- grease filter DHZ2100

** In accordance with the EU-Regulation No 65/2014*

**Series 2, canopy cooker hood, 53 cm,
Stainless steel
DLN53AA50B**

